

MASTER OF SPACE

Tri-lateral Stacker

MODEL:OPD10R

- CAPACITY:1000KGS
- LIFTING HEIGHT UP TO 7.5M
- NEEDED AISLE WIDTH: <1.6M



PT PADMA DYNAMIKA SENTOSA
Member of PADAMAS - forklift

Model				OPD10R	
General Information	1.3	Drive: electric (battery type, mains, ...), diesel, petrol, fuel gas			OPD10R
	1.4	Operator type: hand, pedestrian, standing, seated, order-picker			Tri-lateral stacker
	1.5	Rated capacity/rated load	Q	Kg	1000
	1.6	Load centre distance	c	mm	600
	1.8	Load distance, centre of drive axle to fork	x	mm	160
	1.9	Wheelbase	y	mm	1425
Weight	1.1	Rear overhang (from drive axle to rear extremity)	z	mm	395
	2.1	Service weight (including battery)		kg	4500 (7.5m)
	2.2	Axle loading, laden front/rear		kg	950/1000
Wheel chassis	2.3	Axle loading, unladen front/rear		kg	1100/700
	3.1	Tyres: solid rubber, superelastic, pneumatic, polyurethane			PU
	3.2	Tyre size, front		mm	125x82
	3.3	Tyre size, rear		mm	250x80
	3.5	Wheels, number front/rear (× = driven wheels)		mm	4/1x
	3.6	Tread, front	b10	mm	1312
	4.2	Height, mast lowered	h1	mm	2085/2580/2745/2910/3085/3250/3415/3575
	4.3	Free lift	h2	mm	945/1440/1605/1770/1935/2100/2265/2430
	4.4	Lift	h3	mm	3000/4500/5000/5500/6000/6500/7000/7500

